

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 1990)

Set ¼ sec. post, from which
A Hemlock 24" dia., bears N.15°W., 29 lks. dist.
A Hemlock 14" dia., bears S.30°W., 20 lks. dist.

Survey by Clifford A. Stephens - For: C.H.T. Co. - Aug. 1965
M 22-71

Set 1/2" Iron pipe in creek. Scribed 2 bearing trees:
12" W.H. N.76°30'W., 19.3 ft.
40" W.H. N.65°00'E., 47.1 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew -
Sept. 16, 1969 - C.S. File 54/46-3

Found - 1/2" I.P. at ¼ corner.
12" now 13" Hemlock N.76½°W., 19.3 ft., scribe visible.
40" now 40" Hemlock N.65°E., 47.1 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 12 W
¼ $\frac{S \ 2}{S \ 11}$
1969

Tagged bearing trees. No good trees close to South.
This corner lies in bottom of ravine running S. Orig. call places this corner 7 chs. from stream, not where this corner is set.

Stephen Stys - For: Roseburg Resources Co. - 5/2023 - M182-49

Found - A 2½" brass cap on 1" iron pipe 1969 (properly mkd)
36" Hemlock, with a tag and healed face bears
N.76°30'W., 19.3' 1969

New - A 21" Alder bark scribed "S ¼ S2 BT" with X-chop and tag bears N.24°E. 32.6' to a spike at side center
A 15" Fir, faced & scribed "N ¼ S11 BT" with X-chop and tag bears S.74°E., 43.5' to a spike at side center.
A 8" Alder, bark scribed "N ¼ S11 BT" with X-chop & tag bears S.30°W. 14.1' to a spike at side center

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°40'58.4" W: 124°05'37.4" (Not survey grade)