

PRIMARY CORNER DESCRIPTION C C for Secs. 35 and 36 only (South)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2026)

For closing cor. to Secs. 35 and 36, I set an Alder post, 4 ft. long, 4" sq., 24" in the ground marked CC T22S R12W on N.; S36 on E.; and S35 on W. faces, with 1 notch on E. and 5 notches on W. faces, from which

An Alder 10" dia., bears N.13°E., 87 lks. dist. mkd. T22S R12W S36 BT.

An Alder 6" dia., bears N.67°W., 106 lks. dist. mkd. T22S R12W S35 BT.

No trees in Sec. 2 within limits.

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2102-03)

Intersect the closing cor. of secs. 35 and 36, I destroy all trace of this old cor. and reestablish at the same point as follows:

Set a Cedar post, 3 ft. long, 10" sq., 24" in the ground for closing cor. of secs. 35 and 36, marked CC T22S R12W on N.; S36 on E.; and S35 on W. face; with 1 groove on E. and 5 grooves on W. face, from which

A Fir 7" dia., bears N.77°E., 26 lks. dist. mkd. T22S R12W S36 BT.

A Cherry 4" dia., bears N.5°W., 14 lks. dist. mkd. T22S R12W S35 BT.

Survey by Lloyd D. Smith - For: Oregon State Board of Forestry - Dec. 1985 - M 100-37 (Fd. and used in survey, M 100-38, Jan. 1986)

Set an OSDF 1½" x 36" alum. pipe with a 3 3/4" alum. cap and magnetic insert. Pipe buried 34" in ground.

New BTs -16" Myrtle, bears N.67°E., 33.1 ft. scribed "T22S R12W S36 CC BT", with a bearing tree tag, in place.

29" Fir bears N.46°W., 20.0 ft. scribed "T22S R12W S35 CC BT" with a BT tag in place.

Set a 4"x4"x72" white painted cedar post, bearing N.43°E., 1.1 ft. dist.

NOTE: Stephens 1952 closing corner point for secs. 35 and 36 bears S.89°42'45"W., 209.93 ft. dist. (See CS 63/50-1 Pg. 33)

Old BTs -24" Fir (Stephens) bears N.12°W., 30.0 ft. (now a 28" x 30" high snag in place.)

14" Fir (Stephens) bears N.57°W., 22.6 ft. (now 23", in place) (Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION C.C. for Secs. 35 & 36 only (South)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Fd. OK, Feb. 1992 by H. Wilcox - M 114-75