

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2025)

A Cherry 6" dia. which I mark $\frac{1}{4}$ S on W. face for 1/4 sec. corner, from which

A Cherry 6" dia., bears N.50°E., 8 lks. dist. mkd. $\frac{1}{4}$ S BT

A Cherry 4" dia., bears S.39 $\frac{1}{4}$ °W., 11 lks. dist. mkd. $\frac{1}{4}$ S BT.

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2101-02)

Intersect the old $\frac{1}{4}$ sec.cor. which I change to a cor. for sec. 35. I destroy the marks on E. side of cor. tree; from which

A Cherry 7" dia., bears S.34°W., 11 lks. dist. mkd. $\frac{1}{4}$ S35 BT.

A Cherry 12" dia., bears N.47°W., 14 lks. dist. mkd. $\frac{1}{4}$ S35 BT.

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - Jan. 1986 - M 100-37 and M 100-38

Set an OSDF 1 $\frac{1}{2}$ " x 36" alum. pipe with a 3 $\frac{3}{4}$ " alum. cap and magnetic insert. Pipe is 34" in ground, from which

36" Fir bears S.16°W., 18.5 ft. scribed " $\frac{1}{4}$ S35 BT" with a bearing tree tag in place.

25" Fir bears N.49°W., 13.8 ft. scribed " $\frac{1}{4}$ S35 BT" with a bearing tree tag in place.

Set a 4"x4"x72" white painted cedar post bearing N.21°W., 1.5 ft.