

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26 & 35 only, East

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #534, dated Jan. 12, 1889 (DCSO records Vol. 5 Page(s) 2024)

Set a Maple post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 25, 26, 35 and 36, mkd. T22S S25 on NE.; R12W S36 on SE.; S35 on SW.; S26 on NW. faces, with 1 notch on S. and E. edges, from which

- An Alder 16" dia., bears N.35°E., 45 lks. dist. mkd. T22S R12W S25 BT.
- An Alder 3" dia., bears S.55°E., 233 lks. dist. mkd. T22S R12W S36 BT.
- A Fir 36" dia., bears S.58°W., 17 lks. dist. mkd. T22S R12W S35 BT.
- A Fir 40" dia., bears N.88°W., 23 lks. dist. mkd. T22S R12W S26 BT.

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2100-01)

Intersect the point for old cor. of secs. 26 and 35. I destroy all trace of this old cor. and reestablish at the same point as follows:

- Set A Fir post 3 ft. long, 10" sq., 24" in the ground for cor. of secs. 26 and 35, marked T22S S35 on SW.; and R12W S26 on NW. face, with 1 notch on S. and E. edges, from which
- A Fir 32" dia., bears S.57°W., 17 lks. dist. mkd. T22S R12W S35 BT.
 - A Fir 28" dia., bears N.67°W., 33 lks. dist. mkd. T22S R12W S26 BT.

Fd. OK, 1952 by C. Stephens - C.S File 63/50-1 Page 30

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Geo. Gresham; Dave Brown & Roy Ball - Jan. 1, 1969 - C.S. File 55/101-17

Found original 12x12x3 ft. Fir post, found orig. point with axe work, from which

- 32" Fir bears S.57°W., 17 lks.; now 44", to face closed.
- 28" Fir bears N.67°W., 33 lks.; now 34", face partially rotted, exposed scribe 2.

Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R12W S26 S35 S25 1968 RS 359", 34" in ground, in orig. post hole, in mound of rock, from which a:

- 44" Fir, orig., bears S.57°W., 11.2 ft., scribed BT.
- 34" Fir, orig., bears N.67°W., 21.8 ft., scribed RS 359.

(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. cor. for 26 & 35 only, East

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set 4x4x72" white painted cedar post 1.0 ft. S. of corner pipe.
OSFD metal location poster on 34" Fir BT, N.67°W.
Also BLM poster on 44" Fir BT, S.57°W.

Survey by James McIntosh; J. Ferguson; S. Ditterick; D. Anders - For: Oregon State Board of Forestry - Dec. 13, 1978 - C.S. File 58/164-3

Found - 32" Fir bears S.57°W., 17 lks.; now 58" x 36" high stump in place, face closed.
28" Fir bears N.67°W., 33 lks.; now 38" x 36" high stump in place, portion of face exposed, no scribes visible.

Found 1½" x 36" galv. I.P. in mound of stone, in place, from which a:

44" Fir, orig., bears S.57°W., 11.2 ft.
34" Fir, orig., bears N.67°W., 21.8 ft.
62" x 36" high Fir stump bears N.16½°W., 60.4 ft. to face, scribed RS 1101.
Set 4"x4"x72" white painted cedar post S.38½°E., 2.0 ft. from corner pipe.
OSFD metal location poster on 62"x36" high stump, N.16½°W., 60.4 ft.
Also poster on 58"x36" high Fir stump, S.57°W., 11.2 ft.

Fd. OK, Jan. 1986 by L. Smith - M 100-38