

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600272

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (West)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2099)

At a point 100 ft. above Wind River, I set a sandstone 20x16x12 ins., 15" in the ground for cor. of secs. 24 and 25, marked with 2 notches on S. and 1 notch on E. edge, from which

A Cedar 8" dia., bears N.43°15'E., 53 lks. dist. mkd. T22S R12W S24 BT.

A Spruce 16" dia., bears S.77°E., 50 lks. dist. mkd. T22S R12W S25 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Lloyd D. Smith, transitman - July/Aug. 1969 - C.S. File 55/101-12

Orig. 10x16x12" sandstone 15" in ground, missing, from which
An 8" Cedar bears N.45¼°E., 53 lks.; now 17", in place, partially closed face, scribes ¼ S2 visible.

16" Spruce bears S.77°E., 50 lks.; missing.

Set 1½" x 36" Galv. I.Pipe with 3" bronze cap mkd: "ore. St. Bd. of Forestry S26 T22S S24 S25 R12W 1969 RS 359", 34" in ground, from which

17" Cedar (orig.) bears S.45¼°E., 34.98 ft. scribed RS 359 6 ft. x 15 ft. rock face bears S.75½°E., 28.9 ft. to 6" X; scribed X B0.

Top of spur ridge, course N. & S. bears S.75½°E., 38.9 ft.

Set 4x4x72" white painted cedar post 1.0 ft. SE. of corner pipe.

OSBF metal location poster on orig. cedar, N.45¼°E.