

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1993)

Set post corner of secs. 11, 12, 13 and 14, from which
A Hemlock 24" dia., bears N.70°E., 43 lks. dist.
A Cedar 28" dia., bears S.5°E., 79 lks. dist.
A Fir 36" dia., bears S.68°W., 30 lks. dist.
A Fir 50" dia., bears N.77°W., 62 lks. dist.

Survey By Clifford A. Stephens - For: J. Lightfoot - May/June 1965 - C.S. File 51/321 and M 22-72

Found - Old Cedar limbpost for corner.
Set 3/4" Iron pipe along the side of the old post, from which
A Fir stump now 50" bears N.79°W., 39.0 ft.
A Fir stump now 40" bears S.62½°W., 19.40 ft.
Both original BTs.

Douglas Co. Surveyors Office - L.E. Monrean and Stephen Flause, crew - March 3, 1980 - C.S. File 61/6-6

Found - 3/4" x 34" I.P. firmly set and protruding 10" above ground.
Orig. 24" Hemlock now a badly rotted 14" DBH 10 ft. tall snag, N.68°E., 28.4 ft. (Orig. N.70°E., 28.4 ft.) No blaze or scribe marks found.
Orig. 28" Cedar now 40", down and somewhat rotted near base, Good record bearing and distance to site of uproot, (Rec. S.5°E., 52.14 ft.) No blaze or scribe marks found.
Orig. 36" Fir now a 40" DBH 6 ft. tall rotted stump S.68°W., 21.0 ft., face measurement (Rec. S.68°W., 19.8 ft.) Evidence of double blaze. We open lower blaze and find good BT scribe.
Orig. 50" Fir now a 56" DBH 7 ft. tall stump N.79°W., 40.0 ft. (Rec. N.77°W., 40.9 ft.)
The following trees were marked by Champion International:
A 14" Spruce S.78°W., 33.7 ft. scribed T22S R12W S14 BT on a double blaze.
A 38" Hemlock N.64°W., (Champion tag read N.66°W., we retag to indicate our measured bearing and distance), 26.6 ft. scribed T22S R12W S11 on a single blaze.
A 24" Alder N.18°E., 24.1 ft. scribed T22S R12W S12 BT on a double blaze.
A 27" Alder S.59°E., (Champion tag read S.54°E., we retag), 35.7 ft. scribed T22S R12W S13 bT on a double blaze.
(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

We also tag original BTs except Hemlock, with DCSO
BT tags.
Reference out 3/4" I.P. and remove. Set standard DCSO brass
cap marked: "Douglas County Surveyors Office T22S R12W S11
S12 S14 S13 1980", in pipe's place, then set 3/4" I.P. on
North side of cap.