

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 1993)

-----  
Set ¼ sec. post, from which  
    A Hemlock 15" dia., bears East, 72 lks. dist.  
    A Hemlock 24" dia., bears S.38°W., 48 lks. dist.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy, S.A. Bilow, crew - June 3, 1959 - C.S. File 49/153-1

-----  
Found - 1½" Iron pipe at corner and both orig. BTs.  
    Orig. 15" now 32" Hemlock stump, East 47.5 ft., shows good scribing "¼S".  
    Orig. 24" now 36" Hemlock stump S.38°W., 31.7 ft., shows good scar. I do not open.  
    Bearings check record but distances measured on slope.  
Set Brass cap alongside iron pipe mkd: County Surveyors Office, 1959 ¼ S11|S12 T22S R12W.  
New BT - 12" Hemlock bears S.85°E., 34.5 ft. scribed ¼ S12 CS BT.  
    No trees near to West.  
Corner in bottom of N-S draw.

-----  
Fd. OK, April 1981 by A. Fales - M 87-43  
Fd. BC, 6/2016 - by W.White - M172-10  
Fd. BC, 5/2018 - by W.White - M174-27  
Fd. 7/2021 - J Estabrook - M179-70