

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 1990)

Set post cor. of Secs. 1, 2, 11 and 12, from which
A Fir 24" dia., bears N.65°E., 6 lks. dist.
A Fir 30" dia., bears S.5¼°E., 12 lks. dist.
A Cedar 6" dia., bears S.52°W., 22 lks. dist.
A Hemlock 5" dia., bears N.75°W., 38 lks. dist.

Survey by Wilford N. Haines - Aug. 1960 - C.S. File 51/109-3 and Haines Field Book H-249

Found both original Fir BTs, down. Found scribe on both trees.

Set a 1" x 36" T. Iron for corner $\begin{array}{c|c} S 2 & S 1 \\ \hline S 11 & S 12 \end{array}$ T22S R12W

Scribed -22" Hemlock N.25°W., 20.7 ft. "S-2 T22S R12W BT"
10" Hemlock S.64°E., 14.3 ft. "S-12 T22S R12W BT"
Scribed "BT" on a 24" R.Cedar S.52°W., 14.5 ft. This tree may be orig. SW. tree.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 15, 1969 - C.S. File 54/46-1

Found - T Iron at corner.
10" Hemlock, now stob, S.64°E., 14.3 ft., scribe visible.
22" Hemlock, now stob, N.25°W., 20.4 ft., scribe visible.
24" Cedar, now snag, S.52°W., 14.5 ft., scribe visible "BT", tree downhill.

All trees and stobs have Haines' tags on them.

Set Brass cap at cor. mkd: County Surveyors Office
 $\begin{array}{c|c} T 22 S R 12 W \\ \hline S 2 & S 1 \\ \hline S 11 & S 12 \end{array}$
1969

New BTs -8" Cedar S.81°E., 15.2 ft. mkd. T22S R12W CS BT.
14" Hemlock N.68°W., 6.5 ft. mkd. T22S R12W S2 CS BT.

Stephen Stys - For: Roseburg Resources Co. - 5/2023 - M182-49

Found - A 2½" brass cap on a 1" iron pipe (properly mkd) 1969
Set steel post alongside corner.
A 33" Hemlock, with healed face & tag bears N.68°W., 6.5'. 1969

continued next page

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 31" Cedar with healed face and tag bears S.81°E., 15.2'. 1969

New - A 10' Hemlock, faced & scribed "SE S2 BT" with X-chop and tag bears N.16°W., 20.2' to a spike at side center.

A 21" Hemlock, faced & scribed "SW S1 BT" with X-chop and tag bears N.3°E., 28.8' to a spike at side center.

LAT. & LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°40'58.9" W: 124°05'02 2" (not survey grade)