

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1991)

Set ¼ sec. post, from which
A Fir 36" dia., bears S.45°E., 33 lks. dist.
A Hemlock 36" dia., bears S.25°W., 75 lks. dist.

Survey by Clifford A. Stephens - For: C.H.T. Co. - Aug. 1965
M 22-71

Found - 38" rotten Fir stump, S.45°E., 21.7 ft.
Set 1/2" Iron pipe.
Tagged - 26" W.H. N.23°W., 57.8 ft.

(In Feb. 1971, DCSO set steel fence post alongside I.P.
M 42-27)

Douglas Co. Surveyors Office - John M. Powell, and crew -
Sept. 15, 1969 (added 4/30/2019) - C.S. File 54/46-2

Found - 1/2" Iron pipe.
38" Fir stump S.45°E., 19.3. This tree thought to be orig.
I find no evidence 28" hemlock stump N.23°W., 57.8.
This stump tagged but not scribed.
Not having enough evidence I do not renew this cor. However call on creek hits good.

Stephen Stys - For: Roseburg Resources Co. - 5/2023 - M182-49

Found - A 38" Fir stump, no vis marks, bears S46°E., 21.4'
(S.45°E., 19.3' Per CS 54/46-2)
A 38" spruce with healed face bears S.68°E., 32.6'
(unknown record).
A 30" Hemlock, with healed face bears N.20°E., 10.8'
(unknown record).

Set - A 2½" Aluminum cap on a 5/8"x40" iron rod, mkd
ROSEBURG RESOURCES COMPANY
T22S R12W
¼
S2 o S1
86454PLS
2023

After a diligent search, we could not find the 1/2" iron pipe as set per map file M22-71. I used the bearing and distances from the BT tags on the BTs with an unknown record.

continued next page

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

NEW BTs- A 28" Hemlock, faced & scribed "E ¼ S2 BT" with X-chop and tag bears S.80°W., 5.6' to a spike at side center.
An 18" Hemlock, faced & scribed "W ¼ S1 BT" with X-chop and tag bears N.55°E., 44.3' to a spike at side center.

See 600645 for WC to ¼ Sec. 1 & 2