

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 600645

PRIMARY CORNER DESCRIPTION Wit. Cor. to 1/4 cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - For: Douglas County - C.S. File 56/5-3 and M 42-27

This corner set from survey and is 9.8 ft. South of South rail of RR track, 364.99 ft. North of 1/4 corner set on section line of 1 and 2.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 12 W
S 2 | S 1
1/4
1971

Accessories:

- 5/8" Iron rod, N.49°W., 33.0 ft. This rod 7.3 ft. S. of South rail of RR tracks.
- 5/8" Iron rod, N.2°W., 30.9 ft. This rod 9.2 ft. North of North rail of RR tracks.

Douglas County Surveyors Office - Karen Reed; Terrie Plouff, crew - March 27, 1980 - C.S. File 61/6-20

Found - 1 1/2" x 36" I.P. with no cap. Obviously taken off.
A 5/8" I.Rod bears N.49°W., 33.0 ft. This rod is 7.3 ft. S. of South rail of RR tracks.
A 5/8" I.R. bears N.2°W., 30.9 ft. This rod is 9.2 ft. N. of North rail of RR track.

Set a 1" x 36" Iron pipe with brass cap stamped: "Douglas County Surveyor T22S R12W 1/4 S2 S1 W.C. 365 ft. S. 1980" at the position from iron rods.

Removed old pipe.
No suitable trees.

New Bearing Objects:

- A 5/8" Iron rod bears N.88°E., 46.7 ft. with alum. cap stamped "B0 1"
- A 5/8" Iron rod bears S.7°E., 18.2 ft. with alum. cap stamped "B0 2"

Stephen Stys - For: Roseburg Resources Co. - 5/2023 - M182-49

N.2°04'47"W., 293.33' north of the 1/4 corner Secs. 1 & 2.
Set - 5/8"x30" iron rod w/plastic cap marked "STYS 86454PLS"
New BT - A 15" alder, bark scribed "PL BT" with X-chop & tag bears S.81°W., 25.5' to a spike at side center.
New B0 - A steel U-post bears South 1.5'