

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2111)

-----  
Set a Hemlock post 3 ft. long 15" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S24 on N. and 25 on S. face, from which  
A Fir 40" dia., bears N.88°45'E., 65 lks.. mkd. 1/4 S24 BT.  
A Cedar 36" dia., bears S.16°45'E., 40 lks. mkd. 1/4 S25 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - May 1970 - C.S. File 55/154-2

-----  
Original Hemlock post, missing, from which  
40" Fir bears N.88¾°E., 65 lks.; now 75" stump, scribes 1/4 S exposed.  
36" Cedar bears S.16¾°E., 40 lks; now 42" face grown over.  
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. For. Dept. 1/4 S24 S25 1970 RS 359", 34" in ground, in mound of rock, and from which  
42" Cedar bears N.61°E., 75.1 ft to face, scribed 1/4 S24 BT  
42" Cedar, orig., bears S.16¾°E., 24.0 ft to face, scribed RS 359.  
4x4x72" white painted cedar post 1.2 ft. NE. of corner pipe.  
OSFD metal location poster on 42" Cedar BT, N.61°E., 75.1 ft. dated May 21, 1970.

Jerry Estabrook - For Moore Mill & Lumber - 5/2021 - M179-42

-----  
Found - 3" Bronze cap (properly mkd) and set on a 1½" IP as per record  
A 54" Cedar w/ no visible marks bears N.61°E., 75.1', A tag was added.  
A 68" Fir stump bears N.88¾°E., 42.9', tag was added  
A 55" Cedar stump w/no visible marks bears S.16¾°E., 24.0', a tag was added.  
New BTs- A 17" D.Fir, face scribed "S 1/4 S24 BT" w/X-chop and tag bears N.3°E. 41.5' to a spike at side center.  
A 21" Alder, face scribed "S 1/4 S24 BT" w/X-chop and tag bears N.62°E. 49.2' to a spike at side center  
A 50" Hemlock, face scribed "N 1/4 S25 BT" w/X-chop and tag bears S.18°'W 25.3' to a spike at side center  
A 31" Cedar, face scribed "N 1/4 S25 Br w/X-chop and tag bears S.81°W. 38.7' to a spike at side center  
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS (not survey grade) : N: 43°38'23.5" W: 124°04'25.3"