

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2113)

Set a Chitten post 3 ft. long, 9" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S13 on N. and 24 on S. face, from which
An Alder 28" dia., bears N.10°45'E., 12 lks. dist. mkd. 1/4 S13 BT.
An Alder 30" dia., bears S.31°45'E., 88 lks. dist. mkd. 1/4 S24 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - June 23, 1971 - M 44-33

Set OSBF 1 1/2" x 36" I.P. with bronze cap 32" in ground, from which
11" Alder S.24°W., 41.0 ft.
37" Hemlock N.15°E., 13.5 ft. "RS 359" with yellow metal location poster.
4x4x72" white painted cedar post N.50°E., 2.8 ft.

Brent Bacon - For: Menasha Forest Products - 1/2007 - M152-12

Found - 1 1/2" Iron pipe w/3" brass cap mkd: "1/4 S13 S24 1970"
39" rotten hemlock stump, N.15°E., 13.5'
New BTs- 9" Fir, N.11°E., 6.6', scribed "1/4 S13 BT"
8" Fir, S.63°E., 16.8', scribed 1/4 S24 BT"
8" Fir, S.40°W., 12.5', scribed "1/4 S24 BT"
7" Fir, N.63°W., 9.0', scribed "1/4 S13 BT"