

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 1992)

Crab, 4" dia., is 1/4 sec. corner, from which
A Crab, 3" dia., bears N.70°W., 13 lks. dist.
A Crab 3" dia., bears S.45°W., 9 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - For: Douglas County - Feb/June 1971 - C.S. File 56/5-13 and M 42-27

(Witness Corner)
This corner set from survey, 170.57 ft. E. of 1/4 corner.
Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 12 W
W. C. to
S 1
S 12
1971

New Accessories:
5" Cedar S.20°W., 141.3 ft. mkd. "W.C. 1/4 S12 CS BT".
I. Bolt in SW. cor. of bridge, bears N.33°E., 38.45 ft.
I. Bolt in SE. cor. of bridge, bears N.59°E., 44.74 ft.
1" drill steel, 32.16 ft.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Wit: T.R. Plouff - July 29, 1981 - C.S. File 61/27-27

Found - 1" I.P. with brass cap stamped "County Surveyors Office T22S R12W W.C. to 1/4 S1 S12 1971". Monument set in concrete.

Note: A review of the survey notes filed in the County Surveyors Office shows this monument not set on the section line.

Accessories Found:
Orig. 1/4 cor. BTs not found.
13" R.Cedar (Orig. 5") with well healed blaze, bears S.18 1/2°W., (Rec. S.20°W.), 141.3 ft.
1" I.Bolt at SW cor. of bridge bears N.31 1/2°E., 38.3 ft. (Rec. N.33°E., 38.45 ft.)
1" I.Bolt at SE cor. of bridge bears N.57 1/2°E., 44.6 ft. (Rec. N.59°E., 44.74 ft.)
1" drill steel bears N.87 1/2°E., 32.1 ft. (Rec. N.88°47'E., 32.16 ft.)

(The following accessories are from 1971 but the distances are from the 1981 monument)

1" Drill steel bears N.60°E., 53.9 ft.
(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

13" R.Cedar with healed blaze bears S.17°W., 111.8 ft.

At the true position of Witness Corner as determined by survey, (1971 - M 42-27), WE SET a 1" x 30" I.P. with attached brass cap mkd: "Douglas County Surveyor T22S R12W WC TO 1/4 S1 S12 1981", from which the ¼ cor. S1 and S12 bears S.88°47'W., 170.57 ft.

We leave the 1971 BC monument set firmly and RESTAMP: it is now marked: "Douglas County Surveyor SC7 RESTAMP 1981 1971" This mon. bears N.27½°E., 30.09 ft. of the Witness Corner. (Sketch in file, C.S. 61/27)