

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 644100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only, T23-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #341, dated October 4, 1879 (DCSO records Vol. 5 Page(s) 2019)

Set Cherry post, 4x4 by 5 ft. long in ground for ¼ sec. corner, from which

A Cherry 12" dia., bears S.2°W., 20 lks. dist.

A Cherry 6" dia., bears N.57°W., 19 lks. dist.

Survey by Harry Wilcox - For: International Paper Co. - Feb. 1992 - C.S. File 63/119 and M 114-75

Set 3¼" alum. cap on 3/4" x 24" alum. rod with alum. post and sign alongside. Buried a magnetic marker alongside.

BTs - 28" Fir scribed "¼ S1 BT" with "X" and tags, bears S.84°W., 8.1 ft.

46" Cedar scribed "BT" with "X" and tags, bears N.31°E., 41.1 ft.

26" Maple face scribed "BT" with "X" and tags, bears N.61°E., 72.5 ft.

42" Fir scribed "¼ S1 BT" with "X" and tags bears S.49°E., 36.1 ft.