

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 689500

PRIMARY CORNER DESCRIPTION A.P. on bdy. bet. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1994)

(11.37 chs. West of Rg. line)
Set Witness corner from which
A Fir 60" dia., bears S.40°E., 16 lks. dist.
A Fir 60" dia., bears N.40°W., 31 lks. dist.

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2103 and 2104)

Point for old witness cor. of secs. 7, 12, 13 and 18, the cor. being almost destroyed.
I destroy all trace of the old witness cor. and at the same point, reestablish an Angle Corner as follows:
Set a Hemlock post, 3 ft. long, 8" sq., 24" in the ground for angle cor. marked A P on N. face, from which
A Fir 80" dia., bears N.78°15'W., 124 lks. dist. mkd. AP
BT.
A Fir 68" dia., bears S.83°15'W., 150 lks. dist. mkd. AP
BT.