

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. -
Nov. 20, 1959 - C.S. File 51/62

Set on the true line at the proportioned distance between the
closing cor. for secs. 19 and 30, T22-11 and the closing cor.
for sec. 25 and 36, T22-12, as follows:

Set a 3/4" x 36" Iron rod for 1/4 cor. and mark new trees as
follows:

- Cedar 20" DBH, bears S.73°30'W., 17.7 ft.
- Cedar 20" DBH, bears N.47°30'W., 29.3 ft.

Survey by Arnold G. Gibson - For: Oregon State Board of
Forestry - Restored by W.E. Metcalf - April 1975 - M 55-73

Set OSBF pipe and cap 34" in the ground, from which
22" Cedar S.53½°W., 53.0 ft. "RS 359", with yellow metal
location poster.

- 18" Myrtle N.80°W., 78.2 ft.
- White painted cedar post, S.49°E., 5.9 ft.