

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700241

PRIMARY CORNER DESCRIPTION A.P. on E. bdy Sec 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1875)

Set a stone 14x10x6 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Cedar 8" dia., bears S.65°W., 25 lks. dist. mkd. ¼ S BT
A Chittim 6" dia., bears S.22°E., 29 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1960/Jan. 1961 - C.S. File 42/403-16

(Angle point corner common to secs. 25 and 30, Whipple's 1893 East ¼ cor. Sec. 25, T22-12)
Orig. stone 14 x 10 x 6, now missing, from which a:
8" Cedar bears S.65°W., 25 lks.; now 22", exposed orig. scribed "4", recent scribes BT ¼ S25 T22 R12W 399 outside. (Hootman, LS #399, no record filed)
6" Chittim bears S.22°E., 29 lks.; missing.
Ridge, course East, bears North, 360 lks., in place.
10" Line tree bears North 373 lks.; in place, restored as WP.
Also found a 5/8" Iron pin S.16°E., 3.5 ft. and a 22" Cedar N.49½°W., 25.4 ft. scribed BT ¼ S25 T22S R11.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry AP S25 S30 1960 RS359", 35" in ground in mound of stone, and from which a:
30" Cedar bears N.26°W., 45.9 ft.; scribed AP S25 BT RS359
OSBF metal location poster on Orig. 8" Cedar BT.
We erased the recent scribed "¼" on above trees S.65°W. and N.49½°W.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Restored by Wm. Metcalf with witnesses A.J. Klosterman and J.L. Shumway - June 1974 - C.S. File 57/4-1

Found 14"x10"x6" stone, missing, from which
8" Cedar bears S.65°W., 25 lks.; now 19" in place, face buried by side cast debris from road construction, excavated 7.0 ft. to face, scribes BT exposed.
6" Chittim bears S.22°E., 29 lks.; missing.
10" Line tree bears North, 373 lks.; in place.
Ridge, course East, bears North 360 lks.; in place.
Restoration by Gibson - 1½" x 36" Galv. I.P. with 3" bronze cap, missing, covered by road construction, from which a:
(Cont. Next Page)

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700241

PRIMARY CORNER DESCRIPTION Angle Point on E. bdy. Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

30" Cedar bears N.26°W., 45.9 ft., now 22" in place, face now buried by side cast debris, and inaccessible.
22" Cedar bears N.49½°W., 25.4 ft.; now 18" in place, face buried by sidecast debris, and inaccessible.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Oregon State Board of Forestry T22S S25 R12W AP 1974 RS359" 35" in ground, in fill section of road, and from which a:
19" Cedar, orig. 8", bears S.65°W., 16.5 ft. to face; scribed RS359, 7.0 ft. above old face.
22" Cedar bears N.26°W., 46.5 ft. to face; scribed AP S25 BT, at new ground level.
Set 4"x4"x72" white painted cedar post 8.0 ft. S.47°E. of corner pipe.
OSBF metal location poster on 22" Cedar BT, N.26°W., 46.5 ft.