

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700244

PRIMARY CORNER DESCRIPTION Line tree on E. bdy. Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1875)

-----  
A Fir 10" dia., marked with 2 notches on N. and S. sides.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1960/Jan. 1961 - C.S. File 42/403-10

-----  
Orig. 10" Fir line tree at 36.27 chs. S. on E. bdy. of Sec. 25 (T22-12) with 2 notches on N. and S. sides, now 20" in place, exposed one notch on N. side 67 years old. Top of ridge, E. at 36.40 chs. in place.  
Scribed Line tree as Witness Point, WP S30 on E. side, WP S25 RS359 on W. side, from which a:  
48" Fir bears N.62½°W., 52.0 ft. scribed WP S30 BT.  
43" Fir bears N.46½°E., 18.0 ft. scribed WP S30 BT.

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - May 1991 - M 112-29

-----  
Line tree found, 10" Fir, now 31" in place., from which  
48" Fir, 1960, N.62½°W., 52.0 ft., now 48" x 5 ft. high rotted stump, face closed, in place.  
43" Fir, 1960, N.46½°E., 18.0 ft.; now 48" x 3 ft. high rotted stump, face closed, in place.  
Yellow metal location poster on 13" Hemlock N.72°W., 9.8 ft., now 28" in place.  
Rewitnessed:  
Orange carsonite marker CBM-250R labeled witness post, N.55°W., 48.8 ft. to base, alongside 48" Fir stump BT.  
Orange carsonite marker CBM-250R labeled witness post, N.54°E., 15.4 ft. to base, alongside 43" Fir stump BT.