

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700272

PRIMARY CORNER DESCRIPTION Line Tree on E. Bdy. Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1874)

-----  
Fir 14" dia., marked with 2 notches on N. and S. sides.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1960/Jan. 1961 - C.S. File 42/403-13

-----  
Orig. 14" Fir Line tree at 7.63 chs. S. on the E. bdy. of Sec. 25, T22-12, with 2 notches on the N. and S. sides,; now 28" in place, exposed one notch on S. side, 67 years old. (Ridge top at 6.90 chs. S. on the E. bdy. Sec. 25, now in CCC Rd.)

Scribed Line tree as Witness Point, WP S19 on E. side and WP S25 RS359 on W. side, from which a:

- 41" Fir bears N.88½°E., 56.8 ft., scribed WP S19 BT.
- 36" Fir bears S.43°W., 12.4 ft. scribed WP S25 BT.

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - May 1991 - M 112-29

-----  
14" Fir, original, now missing, from which  
41" Fir, 1960, N.88½°E., 56.8 ft., now 43" x 3 ft. high stump, face rotted, axe work visible, in place.  
36" Fir, 1960, S.43°W., 12.4 ft., now 36" x 6 ft. high stump, face closed, in place.

Set 5/8" x 36" I.R. 48" in ground with yellow plastic cap mkd. LS1101.

- 11" Fir N.76°E., 38.8 ft. scribed "WP S19 BT" with BT tag Orange carsonite marker, CBM-250R labeled Witness Post, N.54°W., 24.3 ft. to base.

White painted cedar post, S.69°W., 5.0 ft.

Corner falls in West edge of Schofield Ridge Road, course N.27°W.