

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1874)

Set a post 4 ft. long, and 4" sq., 2 ft. in ground for cor. to secs. 24 and 25, marked T22S R12W on W.; S24 on N.; and S25 on S. sides, with 4 notches on N. and 2 notches on S. edges, from which
A Chittim 14" dia., bears S.61°W., 14 lks. dist. mkd. T22S R12W S25 BT.
A Hazel 5" dia., bears N.84°W., 5 lks. dist. mkd. T22S R12W S24 BT.
An Alder 20" dia., bears N.40°W., 22 lks. dist. mkd. T22S R12W S24 & 25 BT.

Tied and used in GL0 survey by Charles A. Slang, Deputy Surveyor under Contract #793, dated Feb. 17, 1910 (DCSO records, Vol. 5 Page 1978 (and duplicate page 2105)

Elliott State Forest Boundary Survey - L. Beyers and E. Lough 1939 or 1941 ? - (DCSO Field Book 123 Page 20)

Set a 4" x 4" cedar post 4 ft. long replacing post set by Whipple under Contract #612.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1960 - C.S. File 42/403-15

Original post, now missing, from which a:
14" Chittim bears S.61°W., 14 lks.; now missing.
5" Hazel bears N.84°W., 5 lks.; now 5", down and rotted, no scribes.
20" Alder bears N.40°W., 22 lks.; now 24", exposed portion of T and other scribes, bears N.40°E.
30" Fir line tree bears North 6.16 chs., found in place.
Ridge, course East, bears South 1.80 chs.; in place.
14" Fir line tree bears South 7.63 chs.; found in place.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Board of Forestry T22S R11W R12W S19 S24 S25 1960 RS359", 30" in ground and from which a:
45" Fir bears S.73°W., 15.3 ft. scribed T22S R12W S25 BT RS359.
27" Cedar bears N.56°W., 47.6 ft.; "T22S R12W S24 BT".
24" Orig. Alder BT, bears N.40°W., 14.5 ft.; scribed BT above orig. face.
Set 4"x4"x72" white painted cedar post 1.5 ft. SE of pipe.
OSBF metal location poster on 27" Cedar BT.

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Lloyd D. Smith, LS #1101 - For: Oregon State Board of Forestry - May 1991 - M 112-29

Found - OSBF 3" bronze cap dated 1960 on 1½" x 36" I.P. in place.
20" Alder, original, N.40°W., 22 lks.; now 24" N.50°E., 14.8 ft. to face.
45" Fir, 1960, S.73°W., 15.3 ft.; now 48" x 3 ft. high rotted stump, scribes visible, in place.
27" Cedar, 1960, N.56°W., 47.3 ft.; now 38" scribes visible in place.
White painted 4 x 4 cedar post, SE 1.5 ft. in place.
New Accessories:
24" Cedar S.82°W., 32.9 ft. scribed "T22S R12W S25 BT" and BT tag.
Orange carsonite marked S.71°W., 15.0 ft. to base, alongside 45" Fir BT.

Jerry Estabrook - For: Moore Mill & Lumber Co. - 5/2021 - M179-42

Found - A 3" bronze cap marked as shown and set on a 1½" iron pipe set per CS 42/403.
A 48" rotten stump w/carsonite post bears S.73°W., 15.3'.
A 38" Cedar w/visible scribe in healed face and tag bears S.82°W., 36.5', record 32.9' per M112-29.
A 48" Cedar w/healed face bears N.56°W., 48.4', record 47.6' per CS 42/403 and 47.3' per M112-29, a tag was added.
4X4 Cedar post bears N.90°E., 1.0', record SE 1.5' Per CS 42/403
New BTs- A 9" Hemlock, face scribed "SE S24 BT" with X-chop and tag bears N.66°W., 36.1' to a spike at side center.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS (not survey grade) N: 43°38'25.2" W: 124°03'50.4"