

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700306

PRIMARY CORNER DESCRIPTION Line tree E. bdy. Sec. 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1874)

A Fir 30" dia., marked with 2 notches on N. and S. sides.

Arnold G. Gibson - For: Oregon State Board of Forestry - May 24, 1960 (Filed Jan. 1961) - C.S. File 42/403-12

Orig. 30" Fir Line tree at 73.84 chs. S. on the E. bdy. of Sec. 24 (T22-12) with 2 notches on N. and S. sides, now 48", in place, exposed one notch on S. side, 67 years old.
Scribed Line tree as Witness Point, WP S19 on E. side and WP S24 RS359 on W. side, from which a:
60" Fir bears S.31½°W., 31.0 ft. scribed WP S24 BT.
52" Fir bears N.66½°E., 39.4 ft. scribed WP S19 BT.
OSBF metal location poster on 60" Fir BT.

Survey by Lloyd D. Smith - For: Oregon State Board of Forestry - May 1, 1991 - M 112-29

Line tree found, 30" Fir, orig. now 75", in place.
60" Fir, 1960, S.31½°W., 31.0 ft. now 74" face close, in place. BT tag and yellow metal location poster.
52" Fir, 1960, N.66½°E., 39.4 ft., now 72" face closed, in place with bearing tree tag.