

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700322

PRIMARY CORNER DESCRIPTION Line Tree on E. bdy. Sec. 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1874)

A Fir 12" dia., marked with 2 notches on N. and S. sides.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dec. 1960 - C.S. File 42/403-9

Orig. 12" Line tree at 57.89 chs. S. on E. bdy. Sec. 24 (T22-12), 2 notches N. and S. sides, found uprooted, notches remaining, root hole in place, from which a:

Ridge, course E & W., bears South, 21 lks., now in place.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry W P S24 S19 1960 RS359", 30" in ground, in mound of rock, and from which a

26" double Fir bears S.7°W., 15.2 ft. scribed WP S24 BT RS359.

17" Fir bears S.56°E., 10.3 ft. scribed WP S19 BT.

3' high x 6' wide rock face bears S.39°W., 2.7 ft., scribed "X"

OSBF metal location poster on 26" Fir BT.

Set 4x4x72" white painted cedar post 1.0 ft. East of pipe.

Survey by Lloyd D. Smith - For: Oregon State Board of Forestry - May 1, 1991 - M 112-29

Witness point found (original Whipple line tree, 1893)

Found OSBF P/C, 1960, in place, from which

26" double stemmed Fir, S.07°W., 15.2 ft., now windfall, face rotted.

3' x 6' rock face S.39°W., 2.7 ft., X missing, in place.

White painted cedar post East, 1.0 ft., in place.

Ridge South 21 lks. course East, in place.

Rewitnessed:

7" Spruce N.87½°E., 21.6 ft. scribed "WP S19 BT" with bearing tree tag.

37" Fir S.46°W., 17.1 ft. scribed "WP S24 BT" with bearing tree tag.