

PRIMARY CORNER DESCRIPTION CC for Secs. 13 & 24 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Harvey Gordon, Deputy Surveyor under Contract #69, dated Feb. 2, 1857 - (DCSO records Vol. 5 Page(s) 1855)</p> <p>-----</p> <p>(79.00 chs.) Foot of rocky bluff, set witness to cor. of secs. 13, 18, 19 and 24, from which     An Alder 12" dia., bears N.35°E., 144 lks. dist.     A Maple 24" dia., bears N.20°W., 187 lks. dist. Raised a monument of stone. (80.00 chs.) (South) Cor. of secs. 13, 18, 19 and 24</p>
<p>GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 315, dated Jan. 24, 1879 - (DCSO records Vol. 5 Page(s) 1864)</p> <p>-----</p> <p>The established witness cor. to secs. 13 and 24, which agrees with the notes furnished from Surveyor General's office, viz. Foot of rocky bluff. A stone mound, from which     An Alder 12" dia., bears N.35°E., 144 lks. (Tree now down)     A Maple 24" dia., bears N.20°W., 187 lks.</p>
<p>GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1872)</p> <p>-----</p> <p>At the witness cor. to secs. 13 and 24, which is a mound of stone, from which     A Maple 30" dia., bears N.20°W., 187 lks. dist. mkd. T22S R12W WC S24 BT.     The other BT which is described as an Alder 12" dia. N.35°E., 144 lks. from cor., is gone. (Whipple then goes South 1 chain and establishes a cor. for 13 and 24, which becomes an Angle Point in 1910)</p>
<p>GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 2112)</p> <p>-----</p> <p>At point of intersection, I set a sandstone 15x12x8 ins., 10" in the ground, for closing cor. of Secs. 13 and 24, marked CC on W., with 3 grooves on N. and S. faces, from which     A Spruce 15" dia., bears S.2°W., 26 lks. dist. mkd. T22S R12W S24 BT.     A Maple 5" dia., bears N.60°30'W., 45 lks. dist. mkd. T22S R12W S13 BT. (Point of intersection is 51 lks. N. of an angle corner, former Whipple corner for 13 &amp; 24) (Cont. Next Page)</p>

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION C C for Secs. 13 and 24 only (East)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - June 23, 1971 - M 44-33

-----  
Reestablished, Set OSBF I.P. and 3" bronze cap, 34" in ground, from which  
6" Alder N.45¼°W., 20.2 ft. (RS 359)  
4" Alder S.58°W., 19.9 ft., YMLP  
4"x4"x72" White painted cedar post, NW 2.2 ft.

Brent Bacon - For: Menasha Forest Products - 1/2007 - M152-12

-----  
Found - 1½" iron pipe with 3" brass cap mkd: "T22S S13 S24 R12W T22S S18 R11W 1970"  
14" alder, S.58°W., 19.7' no marks, tag  
9" alder, N.45°W., 19.9', no marks, placed tag  
Wood 4x4 post bears NW 1.7'  
Metal fence post bears SE 0.7'  
Angle point per M44-33 bears S0°21'50"W 33.31'