

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon, Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1854)

Set ¼ sec. post, from which
A Fir 28" dia., bears N.86°E., 12 lks. dist.
A Fir 24" dia., bears S.5°W., 36 lks. dist.

GLO survey by Charles A. Slang, Deputy Surveyor, under Contract #793, dated Feb. 17, 1910 - (DCSO records Vol. 5 Page(s) 1981) (duplicate of Pg. 2108)

Intersect the old ¼ sec. cor. heretofore described which is nearly destroyed.
I destroy all trace of the old cor. and reestablish at the same point as follows:
Set a Spruce post 3 ft. long, 10" sq., 24" in the ground for ¼ sec. cor., marked ¼ S13 on W. face; from which
A Fir 42" dia., bears S.80°W., 44 lks. dist. mkd. ¼ S13 BT
A Fir 36" dia., bears N.49°30'W., 185 lks. dist. mkd. ¼ S13 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - June 18, 1970 - C.S. File 55/154-1

Original post missing, destroyed by Slang in 1910, from which
28" Fir bears N.86°E., 12 lks.; now 36" windfall, axe work visible.
24" Fir bears S.5°W., 36 lks.; now missing.
35" Fir snag 75 ft. tall, bears S.65½°E., 40.1 ft., to face, scribes "¼" visible in open face, no record of restoration.
Restoration by Slang, 1910: Post missing, from which a
42" Fir bears S.80°W., 44 lks.; now 44" stump, in place, scribes visible.
36" Fir bears N.49½°W., 185 lks.; now 42", 56.1 ft. "X" above grown over face.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of For. ¼ S13 1970 RS 359", 34" in ground, and from which
A 45" Fir (Slang's) bears N.49½°W., 55.7 ft. to face; scribed RS 359.
37" Fir bears S.49°W., 85.5 ft. to face; scribed ¼ S13 BT.
Set 4"x4"x72" white painted cedar post 1.0 ft. NE of corner pipe.
OSBF metal location poster on 45" Fir, N.49½°W., 55.7 ft.

continued next page

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Rob Ward - Sept. 24, 2001 - C.S. File 65/37-25

Found - 3" OSBF brass cap on 1" galvanized iron pipe.
44" D.Fir stump with spike in center bears
N.51°16'31"W., 56.55 ft. to spike (healed face)
rec. N.49½°W., 55.7 ft. to face.
36" D.Fir stump with spike in center bears
N.46°06'54"W., 86.31 ft. to spike (healed face)
rec. S.49°W., 85.5 ft. to face.
New - 10" D.Fir bears N.88°W., 4.2 ft. blazed, scribed "¼
S13 BT"
13" D.Fir bears S.48°E. 12.9' blazed, scribed "X BT"
Note - All BTs have red painted band & face plus yellow BT
tag. 5½' gal. steel post adjacent to corner.