

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700518

PRIMARY CORNER DESCRIPTION Wit. Cor. East bdy. Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon, under Contract #52 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1854)

A Fir, 30" dia., is marked for witness cor.
(Corner of secs. 7, 12, 13 and 18 is in ravine)

Wilford N. Haines, #239 - August 1960 - C.S. File 51/109-2

Found - 30" tree marked for Angle Wit. Point on the East line of Sec. 12 at 62.45 chs. This tree is now a stump, it apparently was 24" when scribed, it is now 32" inside the bark. There is an "R" on the stump and the old scar goes down about 10-12". I found an S7 on a log that came off the stump.

I drove a 1" x 1" x 24" T. Iron about 12" in the center of the stump for a W.P. corner.

Drove a 1/2" x 16" Bolt in center of a 42" Fir stump, N.21°W., 23.6 ft.

Drove a 1/2" x 5" lag screw in the center of a 54" Fir stump, N.72°W., 34.6 ft.

Brent Bacon - For: Menasha Forest Products - 2/2005 - M147-32

Found - 1"x1" T-post with 1" brass washer marked "WILFORD N HAINS 239 SURVEY POINT DRAIN ORE" set in 33" rotten fir stump fd. Bt's:

55" rotten fir stump N.72°W., 34.8' to lag screw set in top 40" rotten fir stump, N.21°W., 23.7' to bolt set in top

New BT - 12" Alder, S.32°W., 15.9' bark scribed "WC S12 BT"