

TOWNSHIP 22 RANGE 12 POINT IDENTIFIER # 700551

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T22-11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1957)

At point of intersection, I set a post, 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 6 & 7, marked C C T22S R11W on E.; S6 on N. and S7 on S. with 1 notch on N. and 5 notches on S. faces, from which

A Hemlock 30" dia., bears S.44°E., 67 lks. dist. mkd. T22S R11W S7 BT.

An Alder 3" dia., bears N.84½°E., 84 lks. dist. mkd. T22S R11W S6 BT.

A Spruce 50" dia., bears S.34°W., 153 lks. dist. mkd. T22S R11W CC S6 & 7 BT.

(Point of intersection is 11.02 chs. N. of ¼ sec. cor. Sec. 12 only, T22-12)

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - For: Douglas County - June 8, 1971 - C.S. File 56/5-21 and M 42-27

This corner set from survey.
Set Brass cap at cor. mkd:

		County Surveyors Office	
R	T 22 S	R	
12	S 12	S 6	11
W		S 7	W
		1971	

BTs - 13" Alder S.14°W., 15.3 ft. mkd. T22S R12W S12 CS BT.
8" Alder S.20°E., 17.9 ft. mkd. T22S R11W S7 CC CS BT.

Bearing Object:

5/8" I. Rod N.46°E., 20.0 ft. This rod lies on westerly edge of marshy ground.

Fd. OK, Jan. 1981 by R. Hintz - M 86-60

Fd. and used by BLM survey dated April 1990 thru April 1995 under group #1521. Vol. 51 Pg. 19633

Fd. Ok by Brent Bacon 2/2005 - M147-32