

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 1 only

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Harvey Gordon, Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1853)

 Set ¼ sec. post, from which
 A Fir 36" dia., bears N.75°E., 19 lks. dist.
 An Alder 18" dia., bears S.65°W., 21 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - July 9, 1971 - C.S. File 56/5 and M 42-27

 This corner set from survey.
 Set Brass cap at cor. mkd: County Surveyors Office

R	T 22 S	R
12	S 1 ¼	11
W		W
	1971	

New BTs -5" Hemlock, N.40°W., 49.2 ft. scribed ¼ S1 CS BT.
 18" Hemlock, N.40°E., 11.3 ft. scribed ¼ S CS BT.

Fd. and used by OSHD, June 1987 - DCSO files 0-1

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Jan. 23, 1990 - C.S. File 64/5-4

 Found - 1971 County brass cap on a 1¼" O.D. Iron pipe, protrudes 15" above ground.
 18" now 20" dia., 4 ft. high Hemlock stump, with a rotted partially healed blaze, scribing visible "¼S", bears N.40°E., 11.3 ft. (agrees w/rec.)
 5" now 7" dia., 7 ft. high Hemlock stump with a partially healed double blaze, scribing visible "¼ S1 CS BT", bears N.40°W., 48.3 ft. (Rec. N.40°W., 49.2 ft. dist. is a slope measurement)
 New BTs -11" dia. Alder, bark scribed "¼ S1 CS BT", 4 ft. above ground, bears N.34°W., 23.3 ft.
 8" dia. Spruce, double blazed and scribed "¼ S1 CS BT", bears N.5½°W., 37.8 ft.
 18" dia. Alder, double blazed and scribed "¼ S1 CS BT" bears S.20¼°W., 44.8 ft.
 8" dia. Hemlock, double blazed and scribed "¼ S1 CS BT", bears S.28½°W., 59.3 ft.
 Corner lies on a steep NE slope, approx. 250 ft. South of State Hwy. #38 and 45 ft. easterly of a power line easement clearing.

Fd. OK May 1993, R. Dodge, - C.S. File 63/120-3

(Cont. Next Page)

