

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2118)

-----  
Set qr. sec. post, deposited a quart of pebbles.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1122 - surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17068)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, in concrete, with brass cap mkd: T 22 S R 13 W

1/4  $\frac{S\ 26}{S\ 35}$   
1982

No suitable trees available within limits.

Set a steel fence post alongside the iron post.