

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T23-13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2117)

-----  
Set post cor. of secs. 1, 2, 35 and 36, from which  
A Dwarf Pine 5" dia., bears N.77½°E., 735 lks. dist.  
No other bearing trees near and not a suitable place for trench.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, John P. Lee Cadastral Surveyors, under Group #1037 - surveyed Sept. 1980/July 1982 - (DCSO records Vol. 51 Page(s) 19278)

-----  
Point for the standard cor. of secs. 1, 2, 35 and 36, at record distance; there is no remaining evidence of the original corner.

Set an alum. post 20 ft. long, 5/8" dia., 19½ ft. in the ground, in concrete, with alum. cap mkd.

S C  
T 22 S R 13 W  
S 35 S 36  
S 2 S 1  
T 23 W  
1980

from which  
A Spruce 10" dia., bears S.11½°E., 793 lks. dist. mkd.  
T23S R13W S1 SC BT.  
A Pine 12" dia., bears S.11°W., 1026 lks. dist. mkd. T23W  
R13W S2 SC BT.  
No other suitable trees available.  
Set a 5 ft. steel fence post alongside the iron post.

Cor. Fd. and used in BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1122 - surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17062-63)