

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2117-18)

Set qr. sec. post, drove charred stake, no mound built on account of the sand.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1122 - surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17063)

Point for the 1/4 sec. cor. of secs. 35 and 36, a proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum rod, 22 ft. long, 5/8" dia., 21 ft. in the ground, in concrete, with alum. cap mkd: T 22 S R 13 W
1/4
S 35 S 36
1982

from which

A Spruce 12" dia., bears N.30 1/2° W., 234 lks. dist. mkd. 1/4 S35 BT.

No suitable tree available within limits in sec. 36.

Set a steel fence post alongside alum. rod.