

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2120)

Set post, cor. of secs. 13, 14, 23 and 24, from which
A Pine 4" dia., bears N.26 3/4°E., 65 lks. dist.
A Pine 4" dia., bears N.15°W., 28 lks. dist.
No other bearing trees near.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1122 - surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17067)

Point for the cor. of secs. 13, 14, 23 and 24, at proportionate position. There is no remaining evidence of the original corner.
Set an iron post 28" long, 2 1/2" dia., 26" in the ground in concrete, with brass cap mkd: T 22 S R 13 W
 S 14 | S 13
 S 23 | S 24
 1982
Set a steel fence post alongside the iron post.
No suitable trees available within limits.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 3/31/2004 - C.S. File 67/6-12A

Found - BLM 1982 Brass cap/iron pipe set in concrete, protrudes 2" out of sand.
New - 7" Shore Pine, double blazed & scribed "X S24 CS BT" bears S.67°E., 35.5 ft.
4" Spruce double blazed & scribed "X BT" bears N.61°E., 18.2 ft.
6" Shore Pine double blazed & scribed "S14 CS BT" bears N.70°W., 33.0 ft.
4" Shore Pine, double blazed & scribed "X CS BT" bears S.28 1/2°W., 54.2 ft.