

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 600475

PRIMARY CORNER DESCRIPTION WC MC W Bdy Umpqua River Secs 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 5 Page(s) 2122)

Set meander post at mouth of Umpqua, drove charred stake.

Douglas Co. Surveyors Office - Stephen J. Flause - Jennifer Heller - July 8, 2004 - C.S. File 67/8

Found unrecorded witness corner to the meander corner one the west bdy of the Umpqua River on line between secs. 13 & 14.
Found - 2 1/8" alum. cap on 3/4" I.R. protruding 9", mkd:

STUNTZER ENGINEERING

T22S R13W

WC

14|13

1983

LS 1342

New - A 19" DBH Engelmann Spruce scribed "X CSBT" on a high-low double blaze bears S.80°E., 16.9'.
A 7" DBH Shore Pine scribed "X CS BT" on a high-low double blaze bears S.32°E., 3.5'.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 8/13/2025 - C.S. File 67/61-13

Found - 2 1/8" alum cap on 3/4" iron rod proj 3"
31" Engleman spruce S.80°E. 16.9ft fully healed double blaze. Add 3 1/2" mag nail set at record distance.
14" shore pine S.32°E. 3.5ft fully healed double blaze. Add 3 1/2" mag nail at record distance.

Notes - Mon is approx 85ft south of beach access road.

Compass decl. 14 1/4°E.

Trimble GEO XT Position

43°40'01.573" N.

124°12'13.317" W.