

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 620460

PRIMARY CORNER DESCRIPTION N.W. 1/16 cor. for Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Jan. 14, 1988 - C.S. File 62/49-6 (M101-35)

-----  
Found - Two iron pipes were found in the general vicinity of the NW 1/16 corner, one an I.P. used as the NW 1/16 corner in survey M 56-14 (1½" I.D. I.Pipe protruding 8" above ground, Rec. 2" I.P., source unknown); the other ("a 1½" I.D. I.Pipe with a concrete base, Rec. 2" I.P.) found out of ground, probably used as NW 1/16 cor. in survey C.S. File 51/252. Source unknown. No other monuments found.

Set a 3" dia. Brass cap mkd. "Douglas County Surveyors Office T22S NW 1/16 + S13 R13W 1988", set in concrete filled 8" x 42" concrete bell tile. Monument protrudes 4" above ground. Iron placed inside bell tile for future magnetic detection.

The iron pipe used as NW 1/16 cor. in survey M 56-14 was determined to be in poor relationship with other found monuments along the 1/16 line to the East. It's position was found to be over 16 ft. North of line.

The position of the NW 1/16 cor. is determined by projecting a line from the CN 1/16 cor. westerly through the most westerly monument set by Hintz, C.S. File 51/252, and using the Hintz record distance of 158.8 ft. to reestablish the NW 1/16 corner.

New Accessories:

7" dia. Shore Pine, double blazed and scribed "NW 1/16 S13 CS BT" bears N.64°E., 11.7 ft.

10" dia. Shore Pine double blazed and scribed "NW 1/16 S13 CS BT" bears N.65°W., 18.5 ft.

Power pole bears S.45°W., 6.2 ft.

1½" Iron pipe, I.D., protruding 8' above ground, bears N.10°W., 16.24 ft.

Metal witness post bears South 2.0 ft.

Corner lies on a N-S ridge approx. 40 ft. East of tree line and edge of sand dunes.

FD. Ok by DCS0, July 2004, C.S. File 67/8