

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 1 of T23-13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2117)

-----  
Set qr. sec. post, from which  
A Spruce 8" dia., bears S.89 3/4°E., 1180 lks. dist.  
A Spruce 12" dia., bears N.89½°E., 1178 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, John P. Lee, Cadastral Surveyors, under Group #1037 - surveyed Sept. 1980/July 1982 - (DCSO records Vol. 51 Page(s) 19278)

-----  
Point for the standard ¼ sec. cor. of secs. 1 and 36, at record distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long 2½" dia., 21" in the ground, in concrete, with alum. cap mkd:

S C  
T 22 S R 13 W  
¼ S 36  
S 1  
T 23 S  
1980

from which

A Pine 8" dia., bears S.80°W., 73½ lks. dist. mkd. ¼ S1 SC BT.

A Pine 11" dia., bears N.62½°W., 28 lks. dist. mkd. ¼ S36 SC BT.

Set a 5 ft. steel fence post alongside the iron post.

Cor. Fd. and used in BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1122 - surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17058-59)