

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 2118)

-----  
Set qr. sec. post, from which  
A Spruce 20" dia., bears S.75°E., 283 lks. dist.  
A Pine 15" dia., bears North, 656 lks. dist.

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors, under Group #1122 - surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17064-65)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an alum. rod, 17 ft. long, 5/8" dia., 16 ft. in the ground, in concrete, with alum. cap mkd: T 22 S R 13 W  
1/4  $\frac{S\ 25}{S\ 36}$   
1982

from which  
A Pine 8" dia., bears N.16½°E., 923 lks. dist. mkd. ¼ S25 BT.  
No suitable tree available within limits in sec. 36.  
Set a steel fence post alongside the aluminum rod.