

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 13

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

H. L. Eppstein, County Surveyor - Oct. 1931 - C.S. File 18/20
A&B and M 1-74

-
- Set Iron pipe for center section.
- 30" Spruce BT, leaning to West, N.70°W., 47 ft.
 - 30" Fir BT, N.50°E., 25 ft.
 - 12" Fir BT, S.45°W., 16 ft.
 - 36" Spruce BT, S.15°E., 30 ft.

John E. Hollingsworth, Oregon State parks Survey for Umpqua
Lighthouse State Park - Wit: Mills; Goge; DeSouza; Woods -
August 26, 1977 - C.S. File 58/152 and M 66-64

-
- Found - 6" x 6" concrete post marked "U.S." on the East
side.
- 52", 8 ft. high Spruce stump S.5°E., 31.3 ft.
scribed "BT" on North side.

- Restorations:
- Set steel post with white paddle mkd. "C ¼ S13", from which
16" Fir S.25°W., 21.75 ft. to a date nail on East
side, 4 ft. above ground.
 - 6" Hemlock N.28°30'W., 9.07 ft. to a date nail on
East side, 2 ft. above ground.
 - An iron railroad spike, S.89°30'E., 29.0 ft. in
pavement, 8 ft. from West edge of road.

Douglas Co. Surveyors Office - Randall Smith and Stephen
Flause, crew - Jan. 5, 1988 - C.S. File 62/49-2 (M101-35)

-
- Found - A 6"x6" concrete post with "U.S." mkd. on E. side.
Post protrudes 30" above ground. Possibly set by
Lighthouse Service. (See Dept of Commerce
Lighthouse Service letter between R.R. Tinkham,
Supt. of Lighthouses, and H.L. Eppstein, Co.
Surveyor, in C.S. File 18/20A dated Aug. 22,
1931)
- Iron pipe set per 1931 survey, not found.
 - 30" leaning West, Spruce now rotted stump, no blazes
or scribing found, N.65°W., 45.0 ft. (Rec.
N.70°W., 47.0 ft.) (1931)
 - 36" now 52" dia. 8 ft. high Spruce stump, no blazes
or scribing found, bears S.5°E., 31.3 ft. agrees
well with 1977 record. (Orig. Brg. & dist., 1931,
is S.15°E., 30.0 ft.)
- NE and SW BTs from 1931 are gone.

(Cont. Next Page)

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

16" now 21" dia., D.Fir bears S.25°W., 21.75 ft. dist. to nail on East side of BT, 2½" inside BT, approx. 3 ft. above ground. (agrees well with rec. 1977)

6" now 10" Hemlock bears N.39°W., 9.07 ft. dist. to nail on East side of BT, 1" inside BT, approx. 2 ft. above ground. (Rec. N.28½°W., 9.07 ft) 1977

A RR spike in A.C., bears N.85½°E., 29.0 ft. 8 ft. from West edge of A.C. (Rec. S.89½°E., 29.0 ft.) 1977

Steel post with white paddle mkd. "C ¼ S13" bears S.64°E., 2.1 ft. 1977

No new monument or accessories established.
Corner is in Umpqua Lighthouse State Park at Camp spot T A 7

FD. Ok by DCS0, July 2004, C.S. File 67/8