

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 700103

PRIMARY CORNER DESCRIPTION SW Section cor. Sec. 31, T22-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2069)

At point of intersection (294 lks. North of orig. Tsp. cor) I set a Hemlock post, 5" sq. 5 ft. long, 2 ft. in ground for closing corner to secs. 31 and 6, marked T22S S31 on North; T23S S6 on South; R12W CC on East faces, with 6 notches on North, South and East faces, from which

A Hemlock 12" dia., bears N.22°E., 44 lks. dist. mkd. T22S R12W S31 CC BT.

A Hemlock 12" dia., bears S.72°W., 19 lks. dist. mkd. Ts. 22 and 23 S R12W BT.

A Fir 20" dia., bears S.54°E., 17 lks. dist. mkd. T22S R12W S6 CC BT.

Clear Creek 25 lks. wide running SW passes about 40 lks. NW of this corner.

BLM resurvey by Goodson, etal (under Group #1122 - 1982) "Point for the closing cor. of Tps. 22 and 23 S., R12W., at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established" (DCSO records, Vol. 44 Page 17059)

Survey by Harvey Wilcox, LS #2244 - For: Oregon Dept. of Fish and Wildlife and Douglas County - Dec. 1989 - M 109-50

Set a 3/4" x 30" I.Rod with 2" alum. cap in fill slope of Wildwood Drive.

New BTs -A 15" D.Fir scribed "T22S R12W S31 CC BT" with X at BH and tagged, bears N.62°E., 36.9 ft.

An 8" Alder bark scribed "T23S R12W S6 CC BT" bears S.10°E., 10.6 ft.

FD. Ok by Edward Hall- 7/97 - M 124-77 A-C
Fd. Ok by Ron Quimby, 8/2008 - 2008-0076 A-C

Fd ok by DCSO 6/18/2019 - SJF & JL - New tags - C.S. File 67/46-7