

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30, T22-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #68 dated Feb. 2, 1857 (DCSO records Vol. 5 Page(s) 1987)

Set ¼ sec. post, from which
A Dwarf Pine 5" dia., bears N.14½°E., 22 lks. dist.
A Dwarf Pine 7" dia., bears N.13°W., 38 lks. dist.

GL0 survey by Simon B. Cathcart, Deputy Surveyor, under Contract #559, dated Nov. 15, 1890 - (DCSO records Vol. 5 Page(s) 2081)

At the ¼ cor. of West bdy. of Sec. 30, I find the post down and very rotten. The Pine bearing tree N.13°W., 38 lks. is still green and ¼ S BT very distinct. The pine bearing N.14½°E., 22 lks. dist. is dead but marks very plain ¼ S BT. I set a new post 3x5 ins. sq., 4 ft. long, 2 ft. in ground marked ¼ S on West face.

Fd. 1/2" Iron pipe and BT. - A. Boyer, June 1961 - M 20-69

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, and J. Isgro, Land Dept. - Aug. 15, 1973 - C.S. File 56/35-3

Found - 1/2" I.Pipe recorded on Map M 20-69. No other record
Unrecorded, 6" dead Fir N.59°E., 21.2 ft. scribe
visible "S 0 T22SR12 0S".
Unrecorded, 22" Dwarf Pine N.30°W., 57.8 ft. scribe
visible "¼ S25 T22S R13W", scribed about 30-40
years ago.

No "BT" scar or scribe on either tree. No trace of original
BTs found.
This corner lies approx. 250 ft. S. of power line access road
at South end of Clear Lake.

Fd. OK, Feb. 18, 1975, L.E.M., DCSO - C.S. File 59/46-68

BLM resurvey by Glenn F. Goodson, Rick E. Tawney, Elma Jean Acuna, Cadastral Surveyors - under Group #1122, surveyed Oct. 1982 - (DCSO records Vol. 44 Page(s) 17062)

The 1/4 sec. cor., monumented with an iron pipe, 3/4" dia., firmly set flush with the ground. This monument was reported by Tracy in 1973, as described in a DCSO record, and is accepted as the best available evidence of the original cor. from which bearing trees mkd. by person(s) unknown:
(Cont. Next Page)

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; and 30, T22-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 6" dia., bears N.57 3/4°E., 32 lks. dist. with scribe marks S30 T22 R12 0 visible on an open blaze.

A Pine 20" dia., bears N.30 3/4°W., 87 lks. dist. with scribe marks ¼ S25 T22S R13W CS visible on a partially healed blaze.

At the corner point

Set an iron post 28" long 2½" dia., 25" in the ground with brass cap mkd:

	T 22 S	
	1/4	
R 13 W		R 12 W
S 25		S 30
	1982	

and a new bearing tree

A Fir 10" dia., bears N.43°E., 41 lks. dist. mkd. ¼ S30 BT.

Deposit the local iron pipe inside the iron post.

Fd. OK, Nov. 1992 by J. Minor - M 116-11
Fd. OK, April 1996 by D.Jones - 1996-0111 A&B
Fd. OK by B. Bacon, Feb. 2001 - M136-58