

TOWNSHIP 22 RANGE 13 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp. Corner)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1261)

-----  
Set post cor. of Tps. 21 and 22 S of Rs. 12 and 13 W.  
Raised no mound because the sand is wet and cannot be heaped up.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17187)

-----  
Point for cor. of Tps. 21 and 22 S., Rs. 12 and 13 W., at record distance longitudinally from the meander cor. of secs. 5 and 32, on the left bank of the Umpqua River, S. bdy. of T21S R12W. and record distance latitudinally from the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of T22S R13W.; there is no remaining evidence of the original corner.

Set an aluminum rod, 10 ft. long, 5/8" dia., 9 ft. in the ground, in concrete, with alum. cap mkd.

T 21 S  
R 13 W R 12 W  
S 36 S 31  
S 1 S 6  
T 22 S  
1981

No suitable trees available within limits.  
Set a steel fence post alongside aluminum rod.