

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T23-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2127)

Set a Cedar post 4 ft. long, 24" in the ground 4" sq., for corner to secs. 25, 30, 31 and 36, marked T23S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 5 notches on N. and 1 notch on S. edges, from which
A Fir 20" dia., bears S.45°E., 52 lks. dist. mkd. T23S R1W S31 BT.
A Fir 6" dia., bears N.32°E., 26 lks. dist. mkd. T23S R1W S30 BT.
A Fir 20" dia., bears S.38°W., 7 lks. dist. mkd. T23S R2W S36 BT.
A Fir 24" dia., bears N.57°W., 31 lks. dist. mkd. T23S R2W S25 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2130)

(73.40 chs.)
The old sec. cor. which I destroy.
(80.00 chs.)
Set a post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 25, 30, 31 and 36 mkd. T23S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 1 notch on S. and 5 notches on N. edges, from which
A Cedar 20" dia., bears N.16°E., 36 lks. dist. mkd. T23S R1W S30 BT.
A Fir 30" dia., bears S.56°E., 17 lks. dist. mkd. T23S R1W S31 BT.
A Cedar 20" dia., bears S.72°W., 58 lks. dist. mkd. T23S R2W S36 BT.
A Fir 20" dia., bears N.65°W., 37 lks. dist. mkd. T23S R2W S25 BT.

Georgia Pacific Timber Co. - Sept. 1962, added 1/5/2012 - C.S. File 65/76-3

Found - 1½ Iron pipe
32" fir N.40°W., 27.7 GP tag CS BT
28" hem N.55°E., 36.2 GP tag CS BT
60" fir S.65°W., 28.8 GP tag CS BT.
40" fir S.56°E., 11.2 BLM tag CS BT

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T23-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Wm.W. Glenn and Harvey E. Wofford, Cadastral Surveyors, under Group #345, Surveyed Sept. 1964/July 1966 - (DCSO records Vol. 35 Page(s) 14306)

The Sec. Cor., monumented with an iron pipe, 48" long, 2" dia., firmly set, protruding 24" above ground, from which the remaining original bearing trees:

A burned Cedar stump 32" dia., bears N.16°E., 36 lks. dist. no marks visible.

A Fir 40" dia., bears S.56°E., 17 lks. dist. with scribe marks T23S R1W S31 BT visible on bark blaze.

A burned Cedar snag 30" dia., bears S.72°W., 58 lks. dist., with open and burned blaze.

and locally established bearing trees

Fir 60" dia., bears S.62¼°W., 46 lks. dist., with scribe marks CS BT visible on open blaze.

A Hemlock stump 30" dia., bears S.45½°E., 57 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 23 S	
R 2 W	R 1 W
S 25	S 30
S 36	S 31
1964	

from which

A Fir stump 35" dia., bears N.56°E., 74 lks. dist. mkd. T23S R1W S30 BT.

A Fir stump 36" dia., bears N.43½°W., 44 lks. dist. mkd. T23S R2W S25 BT.

Reset iron pipe alongside the iron post.

The corner is located at the N. edge of heavy timber on a steep NW. slope, bears E. and W.

Fd. OK, March 1973 by Nick Juliano - C.S. File 58/24

David Wellman - For: Weyerhaeuser Co. - 7/8/2004 - C.S. File 65/52-1

Found - 32" Cedar stump, 1964 BLM tag reads "S.16°W., 36 lks." OBT

40" Fir stump, 1986 BLM tag reads "N.56°W., 17 lks." tin cap - OBT

35" Fir stump, 1964 BLM tag reads "S.56°W., 74 lks." scribing visible.

36" Fir stump, 1964 BLM tag reads "S.43½°E., 44 lks." scribing visible.

continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T23-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

	8" Fir, 2000 WEYCO tag reads N.21°E., 6.7 ft. to "W" nail - open face. (No rec.)
	9" Fir, 2000 WEYCO tag reads S.33°E., 7.7 ft. to "W" nail - open face. (No rec.)
	9" Fir, 2000 WEYCO tag reads S.25°W., 15.3 ft. to "W" nail - open face. (No rec.)
New -	6' metal fence post set 1.0 ft. north.