

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Secs. 30; & 25 T23-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2128)

Set hemlock post, 3 ft. long 3" sq., 24" in the ground for ¼ sec. corner marked ¼ S on W face, from which
 A fir, 8" dia., bears S.60°E., 8 lks., mkd: ¼ S BT.
 A fir, 5" dia., bears West, 14 lks., mkd: ¼ S BT

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2130-1)

(Pg. 2130) Could find no trace of old ¼ sec. cor.
(Pg. 2131) Set basalt stone 12x12x6", 9" in the ground, mkd. ¼ on W face for ¼ sec. cor. on old blazed line, from which
 A fir, 7" dia., bears S.41½°W., 16 lks., mkd: ¼ S BT.
 A hemlock, 7" dia., bears S.17½°E., 28 lks., mkd: ¼ S BT.

Georgia Pacific Timber Co. - Sept. 1962, added 1/5/2012 - C.S. File 65/76-3

Found - 1½ IP
 24" Fir S.70°W., 4.0 BK tag
 12" Hem S.17°E., 18.5 BK tag.

Dan Baker - For: Weyerhaeuser Co. - 9/30/2011 - C.S. 65/76-1

Found - 1½ iron pipe (bent)
 17" hemlock stump S.13°E., 18.7' - original BT
 24" fir stump S.64°W., 4.2' (Booth Kelly BT)
 Nothing set
New - 16" Fir, N.51°E., 34.5' to spike in side - scribed "¼ S30 BT"
 12" cedar, S.21°E., 19.5' to spike in side - scribed "¼ S30 BT"
 21" fir, S.83°W., 19.7' to spike in side - scribed "¼ S25 BT"
 15" fir N.13°W., 19.5' to spike in side - scribed "¼ S25 BT"

Dan Baker - For: Weyerhaeuser Co. - 11/2021 - M180-19

Condition report
Found - 1½ iron pipe (bent)
 17" rotten hemlock stump, S.13°E., 18.7' to center
 OBT
continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Secs. 30; & 25 T23-2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

24" rotten fir stump, S.64°W., 4.2' to center.
19" fir, N.51°E., 34.5' to spike side/center
16" cedar, S21 E, 19.5' to spike side/center
24" fir, S.83°W., 19.7' to spike side/center
17" fir, N.13°W., 19.5' to spike side/center