

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2158)

-----  
Set a basalt stone, 12x10x8 ins., 9 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on N. face; from which  
A Fir, 6" dia., bears N.65°W., 9 lks., mkd: 1/4 S BT.  
A Fir, 9" dia., bears S.58 1/2°W., 27 lks., mkd: 1/4 S BT.

BLM Resurvey by Wm.W. Glenn and Harvey E. Wofford, Cadastral Surveyors, under Group #345, Surveyed Sept. 1964/July 1966 - (DCSO records Vol. 35 Page(s) 14329)

-----  
The 1/4 sec. cor. of secs. 30 & 31, monumented with the orig. basalt stone, 12x10x8 ins., loosely set, 2" in the ground, marked 1/4 on the N face, from which the OBTs:  
A Fir stump, 8" dia., bears N.65°W., 9 lks., with scribe marks 1/4 S visible on opened blaze.  
A root hole bears S.58 1/2°W., 27 lks., with down fir alongside, 12" dia., with healed blaze.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap marked:  
T23S R1W  
1/4 S 30  
S 31  
1964  
from which  
A Fir, 23" dia., bears N.18°W., 51 1/2 lks., mkd: 1/4 S30 BT.  
A Fir, 21" dia., bears S.6 1/2°E., 48 lks., mkd: 1/4 S31 BT.  
Deposit the corner stone alongside the iron post.

David Wellman - For: Weyerhaeuser Co. - 7/8/2004 - C.S. File 65/52-2

-----  
Found - 2 1/2" iron pipe w/BLM brass cap dated 1964, at grade.  
34" Fir, 1964 BLM tag reads "S.18°E., 51 1/2 lks., closed face.  
24" Fir, 1964 BLM tag reads N.6 1/2°W., 48 lks., closed face.  
25" Fir, 1964 BLM tag reads S.65°E., 9 lks., closed face.  
New - 24" Fir, N.59 1/2°E., 18.8 ft. to spike set side center  
- scribed "1/4 S30 BT"  
6' metal fence post 1 ft. south

continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Dan Baker - For: Weyerhaeuser Co. - 12/2011 - M163-26

-----

Found - 3¼" BLM Brass cap "1964"  
26" fir, N.60°E., 20.0' (rec. 18.8') 2004  
25" fir, S.5°E., 21.1' - 1964  
35" fir, N.20°W., 33.6' - BLM BT  
29" fir, N.65°W., 12.3' - orig. unknown  
Set - 6 ft. steel post alongside corner.