

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2156)

-----

Set sandstone 12x10x6 ins. 9 ins. in the ground, marked with 1 notch on S & 5 notches on E edges, for cor. to secs. 29, 30, 31, & 32, from which

- A Hemlock, 18" dia., bears N.76°E., 67 lks., mkd: T23S R1W S29 BT.
- A Fir, 36" dia., bears S.22½°E., 19 lks., mkd: T23S R1W S32 BT.
- A Fir, 30" dia., bears S.82½°W., 15 lks., mkd: T23S R1W S31 BT.
- A Fir, 40" dia., bears N.16°W., 57 lks., mkd: T23S R1W S30 BT.

BLM Resurvey by Wm.W. Glenn and Harvey E. Wofford, Cadastral Surveyors, under Group #345, Surveyed Sept. 1964/July 1966 - (DCSO records Vol. 35 Page(s) 14328)

-----

The cor. of secs. 29, 30, 31, & 32, monumented with the orig. sandstone, now broken & loosely set, marked with 5 notches on the E & 1 notch on the S. face, from which the OBTs:

- A Hemlock, 32" dia., bears N.76°E., 67 lks., with fragmentary scribe marks visible on partially healed blaze.
- A Fir, 43" dia., bears S.22½°E., 19 lks., with healed blaze.
- A Fir, 33" dia., bears S.82½°W., 15 lks., with fragmentary scribe marks visible on opened blaze.
- A Fir, 58" dia., bears N.16°W., 57 lks., with healed blaze.

At the corner point  
 Set an iron post, 28" long, 2½" dia., 16" in the ground, to bedrock & in a mound of stone, 3 ft. base, to top, with brass cap marked:

|  |             |             |
|--|-------------|-------------|
|  | T23S        | R1W         |
|  | <u>S 30</u> | <u>S 29</u> |
|  | S 31        | S 32        |
|  | 1964        |             |

Deposit the corner stone alongside the iron post.

Dan Baker - For: Weyerhaeuser Co. - 12/2011 - M163-26

-----

Found - ¾" BLM Brass cap "1964"  
 39" capped fir stump (5' high) S.84°W., 10.5' - orig. BT.  
 36" capped fir stump (5' high) S.24°E., 12.5' - orig. BT.

continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

|       |  |
|-------|--|
| New - | 5" Fir, S.24°W., 5.3' - scribed "S30 BT" & "X" at breast height. |
|       | 6" Fir, N.63°W., 54' - scribed "S31 BT" & "X" at breast height.  |
| Set - | 6 ft. steel post alongside corner.                               |