

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

**THIS CORNER ON THE COUNTY LINE - CHECK W/LANE CO.
TO SEE IF THERE ARE ANY OTHER SURVEYS THAT EFFECT
THIS CORNER**

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2157)

Set basalt stone 12x10x8" 9" in the ground, mkd ¼ on N face for ¼ sec. cor., from which

A fir, 6" dia., bears N.65°W., 9 lks., mkd: ¼ S BT.

A fir, 9" dia., bears S.58½°W., 27 lks., mkd: ¼ S BT.

Dan Baker - For: Weyerhaeuser Co. - 12/2011 - M163-26

Found - 28" hemlock, S.50°E., 6.0' to center - orig. BT

Set - 5/8"x36" rebar with 2½" alum. cap. Stamped:

T23S R1W

¼

S30|S29

PLS 1978

2011

10" hemlock, N.56°E., 25.6' - scribed "¼ S29 BT"

9" hemlock, S.37°W., 28.8' - scribed "¼ S29 BT"

14" cedar, N.73°W., 35.3' - scribed "¼ S29 BT"

Note - 60" broken fir, bears North 6.0 ft. (possible line tree as called in orig. note at North 9 lks)

Set - 6 ft. steel post alongside corner