

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2148)

Set a post 4 ft. long 4" sq. 24" in the ground for cor. to secs. 27, 28, 33 & 34 mkd. T23S S27 on NE, R1W S34 on SE, S33 on SW, and S28 on NW, faces with 1 notch on S and 3 notches on E. edges from which
A Hemlock, 12" dia., bears N.88°E., 45 lks., mkd: T23S R1W S27 BT.
A Hemlock, 24" dia., bears S.53°E., 80 lks., mkd: T23S R1W S34 BT.
A Cedar, 12" dia., bears S.80°W., 33 lks., mkd: T23S R1W S33 BT.
A Fir, 60" dia., bears N.58°W., 58 lks., mkd: T23S R1W S1 BT.

BLM Dependent resurvey by Harold Corbin, Cadastral Surveyor, under Group # 345 & 350, surveyed April/Oct. 1960 - (DCSO records Vol. 31 Page(s) 12975)

The cor. of secs. 27, 28, 33, & 34, determined at the record distances from the remaining orig. BTs:
A Hemlock, 23" dia., bears N.88°E., 45 lks., with healed blaze.
A Cedar, 35" dia., bears S.60°W., 33 lks., with scribe marks TS R1W visible on partially opened blaze. (Rec. bearing S.80°W.)
A Fir, 65" dia., bears N.58°W., 58 lks., with bark scribe mark T visible.

At the corner point
Set an iron post, 28" long, 2½" dia., 25" in the ground, & in a mound of stone, 2 ft. base to top, with brass cap marked:
T23S R1W
S 28|S 27
S 33|S 34
1960

from which
A Hemlock, 9" dia., bears S.26°E., 37 lks., mkd: T23S R1W S34 BT.
A Hemlock, 6" dia., bears S.43°W., 41 lks., mkd: T23S R1W S33 BT.