

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2149)

Set a basalt stone, 12x12x12 ins., 9 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on W. face; from which
A fir, 8" dia., bears N.45°E., 10 lks., mkd: 1/4 S BT.
A Fir, 12" dia., bears N.36°W., 8 1/2 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Harold Corbin, Cadastral Surveyor, under Group # 345 & 350, surveyed April/Oct. 1960 - (DCSO records Vol. 31 Page(s) 12976)

The 1/4 sec. cor. of secs. 27 & 28, monumented with the orig. basalt stone 12x12x12 ins. firmly set 6" above the ground, from which the only remaining OBT:

A Fir, 20" dia., bears N.36°W., 8 1/2 lks. with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap marked:
T23S R1W
1/4
S 28|S 27
1960

from which
A Fir, 25" dia., bears S.87 1/2°E., 40 lks., mkd: 1/4 S27 BT.
Deposit orig. corner stone alongside iron post.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.