

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Secs. 34; & 3 T24-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2137)

Set basalt stone, 15x10x5" 10" in the ground, marked ¼ on N face, for ¼ sec. cor., from which
A fir, 24" dia., bears N.60°E., 45 lks., mkd: ¼ S BT.
A fir, 40" dia., bears S.80°E., 39 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23395-6)

The ¼ sec. cor. of secs. 3 & 34, on the S. bdy. of the Tp., determined at record bearing and from the remains of an original bearing tree

A fir stump, 40" dia., bears S.80°E., 25.7 ft., with scribe marks BT visible on a partially opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with a brass cap mkd.

T23S R1W
¼ $\frac{S\ 34}{S\ 3}$
T 24 S
2015

from which

A fir, 16" dia., bears N.68¾°E., 13.7 ft., mkd. ¼ S34 BT.

A fir, 14" dia., bears S.21¼°W., 24.6 ft., mkd. ¼ S3 BT.

The geographic position in NAD 1983 (2011)

Latitude: 43°31'23.97" N. Longitude: 122°47'28.13" W