

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2148)

Set a basalt stone, 15x10x5 ins., 10 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on N. face; from which
A Fir, 20" dia., bears S.18°W., 38 lks., mkd: 1/4 S BT.
A Fir, 10" dia., bears N.40°E., 47 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Harold Corbin, Cadastral Surveyor, under Group # 345 & 350, surveyed April/Oct. 1960 - (DCSO records Vol. 31 Page(s) 12975)

The 1/4 sec. cor. of secs. 27 & 34 determined at the record distances from the orig. BTs:
A Fir, 22" dia., bears N.50°E., 47 lks., with healed blaze. (Rec. bearing, N.40°E.)
A Fir, 26" dia., bears S.3°W., 38 lks., with healed blaze. (Rec. bearing S.18°W.)
At the point
Set an iron post, 28" long, 2 1/2" dia., on bedrock, and in a mound of stone, 5 ft. base to top, with brass cap marked:
T23S R1W
1/4 S 27
S 34
1960