

PRIMARY CORNER DESCRIPTION Cor. Secs. 34, 35; 2, & 3 T24-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2138)

-----

Set basalt stone, 12x10x6" 9" in the ground, for cor. to secs. 2, 3, 34, & 35, marked with 4 notches on W & 2 notches on E edges, from which

- A fir, 24" dia., bears N.22°E., 122 lks., mkd: T23S R1W S35 BT.
- A fir, 6" dia., bears S.80°E., 15 lks., mkd: T24S R1W S2 BT.
- A fir, 6" dia., bears S.5°W., 64 lks., mkd: T24S R1W S3 BT.
- A fir, 36" dia., bears N.1°W., 184 lks., mkd: T23S R1W S34 BT.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 2338)

-----

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented a basalt stone, 12x10x6", firmly set, projecting 6" above ground, mkd. with 4 notches on the W. side and 2 notches on the E. side visible, from which the remaining original bearing trees

- A fir, 43" dia., bears N.22°E., 80.5 ft., with a healed blaze.
- A fir, 32" dia., bears S.7¼°W., 42.2 ft., with a healed blaze. (Record, S.5°W.)
- A fir, 39" dia., bears N.1°W., 115.0 ft., with a healed blaze. (Record, 121.4 ft.)

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 6" in the ground, in a mound of stone, 3 ft. base, to the top, with a brass cap mkd.

```

T 23 S R 1 W
  S 34 | S 35
  S 3  | S 2
      T 24 S
      2015

```

from which

- A fir, 11" dia., bears S.58¼°E., 21.4 ft., mkd. T24S R1W S2 BT.

Bury the basalt alongside the stainless steel post.