

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2144)

Set a basalt stone, 18x14x12 ins., 14 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on W. face and raised mound of stone 3 ft. base, 2 ft. high alongside there being no live trees near, pits impracticable.

DCSO not fd 10/7/1970 C.S. File 54/27-154 - Due to steepness of ground and age of survey, corner apparently slid away and couldn't be found.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23389)

Point for the 1/4 sec. cor. of secs. 34 & 35, at proportionate dist.; there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with a brass cap mkd.

T 23 S R 1 W
 1/4
 S 34 | S 35
 2015

from which
 A fir, 12" dia., bears S.62 1/2°E., 23.2 ft., mkd. 1/4 S35 BT.
 A fir, 12" dia., bears S.62°W., 13.3 ft., mkd. 1/4 S34 BT.
From the corner
N.2°22'08"W., 25 ft., center of Oakland to Bohemian Mine trail, dirt surface, 10 ft. wide, bears N.75°W. and S.75°E.